






	1		2
品牌	BOYA	长丰型号	BY-BM3030

7			8	
修改名称	版本	变更内容	变更日期	变更担当
BY-BM3030说明书	V02	内容更新	2020-6-4	吴蒙蒙

<div></div> <div></div> <div><h3>BY-BM3030</h3><p>On-Camera Shotgun Microphone</p><p>机顶枪型超心型麦克风</p><p>Instruction Manual</p><p>说明书</p></div>	<p>Thanks for choosing BOYA!</p> <p>The BOYA BY-BM3030 is a Super-cardioid condenser shotgun microphone, 3.5 mm mini plug connector making it compatible with DSLRs, camcorders, audio recorders that equipped with 3.5mm mic input. It features an integrated shock mount that can be mounted on a camera or boompole, and is ideal for interviews, ENG and more.</p> <p>The high-quality and uni-directional condenser capsule will decrease ambient noise while recording sound with greater clarity.</p> <p>This mic includes a foam windscreen and fur windscreen that helps to decrease vocal plosives and wind noise when recording dialog and powered by two pieces of AA batteries (not included) for up to 150 hours.</p> <p>PACKAGE CONTENTS</p> <ul style="list-style-type: none">• Microphone• Foam windscreen• Fur windscreen• Carrying pouch• Quick Setup Guide	<p>INSTRUCTURE</p> <ol style="list-style-type: none">1. Power Indicator2. Power ON3. Power OFF4. 3.5mm headphone Jack5. Foam windscreen6. Battery Compartment7. Shock Mount8. Camera Shoe Mount with 1/4" Thread9. 3.5mm TRS Audio cable <p>Note: Cable in illustrations is shown shorter for clarity. The actual cable is longer than the one pictured.</p> <div></div>	<p>HOW TO USE</p> <p>Installing the battery</p> <ol style="list-style-type: none">1. Press the bottom of battery compartment lid down and lift it up.2. Insert the AA battery. Make sure that the + and – signs match the symbols in the compartment.3. Replace the battery compartment lid. <div></div>	<p>SETTING UP YOUR MICROPHONE</p> <p>To attach your microphone to a camera:</p> <ol style="list-style-type: none">1. Loosen the locking knob, then slide your microphone's shoe mount onto your camera.2. Tighten the locking knob to secure your microphone.3. Connect the 3.5 mm audio cable to your camera. <p>To attach your microphone to a tripod:</p> <ol style="list-style-type: none">1. Tighten the microphone to the 1/4" screw on a tripod or tripod plate. See the instructions that came with your tripod for more information.2. Connect the 3.5 mm audio cable to your camera. <div></div> <p>1/4" mounting threads</p> <p>USING YOUR MICROPHONE</p> <ol style="list-style-type: none">1 Turn on your camera.2. Slide the power switch to ON, the LED indicator lights up.3. Aim the microphone at the sound source and away from unwanted sound sources (only if used on a tripod). <p>Tip: If using a tripod, the microphone could be held below or above as well as straight in-front of the sound source.</p> <ol style="list-style-type: none">4. Slide the power switch to OFF when you finished recording.	<p>TROUBLESHOOTING</p> <table><tr><th>Problem</th><th>Solution</th></tr><tr><td>No sound was recorded</td><td>Make sure that two fresh AA batteries are installed and correctly oriented in the battery compartment. Make sure the power switch on the microphone is set to the ON position and the LED indicator is on. Make sure that 3.5mm mini plug is connected to the correct AUDIO INPUT jack on the device to which you are recording.</td></tr><tr><td>The sound is distorted</td><td>Make sure the 3.5mm mini plug is fully plugged into the audio input jack of your camera or recorder. If your camera or device has an input control, decrease the mic gain (audio input level) on your camera until the meter reads slightly below peak level at the lowest point of the audio. Reposition the BY-BM3030 further away from the sound source.</td></tr><tr><td>The recording level is too low</td><td>If your camera or device has an input control, increase the mic gain (audio input level) on your camera until the meter reads slightly below peak level at the loudest point of the audio. Reposition the BY-BM3030 closer to the sound source.</td></tr><tr><td>Sound is distorted</td><td>Make sure the microphone boost is switched off, move away from the subject, consult camera owner's manual for audio recording settings.</td></tr><tr><td>The microphone is stuck in the camera's shoe mount</td><td>Make sure the locking wheel is fully loosened.</td></tr></table> <p>MAINTAINING YOUR MICROPHONE</p> <ul style="list-style-type: none">• Keep your microphone away from dust, moisture, or water.• To clean the housing, wipe with a dry micro-fiber cloth to remove dust.• Store your microphone in the included pouch to protect it from dirt and dust.	Problem	Solution	No sound was recorded	Make sure that two fresh AA batteries are installed and correctly oriented in the battery compartment. Make sure the power switch on the microphone is set to the ON position and the LED indicator is on. Make sure that 3.5mm mini plug is connected to the correct AUDIO INPUT jack on the device to which you are recording.	The sound is distorted	Make sure the 3.5mm mini plug is fully plugged into the audio input jack of your camera or recorder. If your camera or device has an input control, decrease the mic gain (audio input level) on your camera until the meter reads slightly below peak level at the lowest point of the audio. Reposition the BY-BM3030 further away from the sound source.	The recording level is too low	If your camera or device has an input control, increase the mic gain (audio input level) on your camera until the meter reads slightly below peak level at the loudest point of the audio. Reposition the BY-BM3030 closer to the sound source.	Sound is distorted	Make sure the microphone boost is switched off, move away from the subject, consult camera owner's manual for audio recording settings.	The microphone is stuck in the camera's shoe mount	Make sure the locking wheel is fully loosened.
Problem	Solution																
No sound was recorded	Make sure that two fresh AA batteries are installed and correctly oriented in the battery compartment. Make sure the power switch on the microphone is set to the ON position and the LED indicator is on. Make sure that 3.5mm mini plug is connected to the correct AUDIO INPUT jack on the device to which you are recording.																
The sound is distorted	Make sure the 3.5mm mini plug is fully plugged into the audio input jack of your camera or recorder. If your camera or device has an input control, decrease the mic gain (audio input level) on your camera until the meter reads slightly below peak level at the lowest point of the audio. Reposition the BY-BM3030 further away from the sound source.																
The recording level is too low	If your camera or device has an input control, increase the mic gain (audio input level) on your camera until the meter reads slightly below peak level at the loudest point of the audio. Reposition the BY-BM3030 closer to the sound source.																
Sound is distorted	Make sure the microphone boost is switched off, move away from the subject, consult camera owner's manual for audio recording settings.																
The microphone is stuck in the camera's shoe mount	Make sure the locking wheel is fully loosened.																

技术要求:

- 1、表面无色差
- 2、无正负公差
- 3、包装标注尺寸为内尺寸

长丰影像
2020-6-4
吴蒙蒙

JIAYZ 长丰 深圳市长丰影像器材有限公司					
子件名称	BY-BM3030 说明书	版本	V02		
子件编号	1F0300300122	材质	105g双铜纸	双面印刷	6折页
尺寸	105x178	比例	1:1	单位	mm
设计/日期	吴蒙蒙 2020-6-4	审核	暂无	核准/日期	赵宏亮